

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER : 62004737
PUBLICATION DATE : 10-01-87




APPLICATION DATE : 28-06-85
APPLICATION NUMBER : 60143421

APPLICANT : HITACHI CHEM CO LTD;

INVENTOR : NAKAHARA TAKESHI;

INT.CL. : C08L 25/04 C08K 3/22 C08K 5/06

TITLE : FLAME-RETARDING RESIN
COMPOSITION



ABSTRACT : PURPOSE: To resin composition excellent in flame retardancy, impact resistance, flow, weathering resistance and heat resistance, prepared by mixing styrene resin with a specified flame-retarding agent and Sb_2O_3 .

CONSTITUTION: 1 equivalent of a halogenated bisphenol A epoxy resin is reacted with 0.6~1 equivalent of a halogenated phenol (e.g., tribromophenol) at 100~230°C in the presence of 0.01~2wt%, based on said resins, basic catalyst (e.g., LiOH) to obtain a flame retardant (B) obtained by mixing 60~100mol% compound (a) and 40~0mol% compound (b) at a molar ratio of 6~1/4~0, said compound (a) being represented by formula I (wherein Y_1 if formula II, X is Br or Cl, R is a lower alkyl, i is 0~4, j is 1~5, $i+j \leq 5$, Y_2 is Y_1 or glycidyl, and m are each 1~4, n is 1~30 on the average and Y_2 is Y_1), and said compound (b) being represented by formula I (wherein Y_2 is a glycidyl group). 100pts.wt. styrene resin 9A) (e.g., PS) is mixed with 3~40pts.wt. component B and 2~10pts.wt. Sb_2O_3 . If necessary, an UV absorber, a plasticizer, a colorant, etc., are added to the obtained mixture.

COPYRIGHT: (C)1987,JPO&Japio